

Camera System 7" Touch 1080P Shutter Camera 6IR 20m 4CH

SKU

18334

This premium HD camera system with a 7-inch touch monitor, 1080P electric shutter camera, and 20 m cable is designed for heavy-duty vehicles, trucks, and construction machinery where visibility, safety, and reliability are essential. The 13003 camera features an automatic electric shutter that protects the lens from rain, dirt, and dust – ideal for harsh environments. It delivers crisp 1080P images with a 130° viewing angle, 6 IR LEDs, and IP69K waterproof protection for all weather conditions. The 10326 touchscreen monitor supports up to four cameras simultaneously and offers flexible split-screen display via a clear and responsive interface.

The included 20 m 4PIN cable ensures a stable, interference-free signal – ready for professional installation.

Part Numbers

Monitor: 10326

Camera: 13003

Cable: 19320

Compatible extra cameras: All wired models



Teknisk information

Monitor – Specifications

Part number: 10326

Display: 7" IPS touch screen

Resolution: 1024 x 600

Video input: 4 channels (1080P / 960P / 720P / CVBS)

Display modes: 1 / 2 / 3 / 4 split view

OSD functions: Mirror/normal, delay, priority, scaling, memory retention

Brightness: 600 cd/m² (auto-adjusting)

Vibration rating: 5G (GB/T 2423.56-2023)

Operating voltage: DC 11–32 V

Operating temperature: -20 °C ~ +70 °C

Storage temperature: -30 °C ~ +80 °C

Dimensions (LxWxH): 218 x 150 x 54 mm

Camera – Specifications

Part number: 13003

Resolution: 1080P (1920 x 1080)

Viewing angle: 130°

IR range: Up to 15 m (6 IR LEDs)

Function: Electric shutter (motorized protection)

Waterproof rating: IP69K

Operating voltage: DC 12V ±10% (powered by monitor)

Operating temperature: -20°C ~ +60°C

Storage temperature: -30°C ~ +70°C

Vibration resistance: 5G (GB/T 2423.56-2023)

Dimensions (WxHxD): 76 x 77 x 66 mm

Cable – Specifications

Part number: 19320

Connector: 4PIN aviation connector (male–female)

Length: 20 m