

Kamerasystem 10.1" 1080P Wireless inkl. kamera 23311 QUAD 4CH

SKU

28351-C

This is a complete wireless HD rear-view camera system with a 10.1-inch IPS monitor and a 1080P camera with a built-in antenna. The system offers up to 200 m wireless transmission range in clear line of sight and uses automatic frequency hopping for a stable and interference-free signal. The monitor supports 1/2/3/4 split-screen display and features a clear OSD menu for mirror/normal image switching, scaling, and reverse delay. The camera provides a 130° field of view, 10 m IR night vision, and an IP69K waterproof rating, making it reliable in all weather conditions.



Teknisk information

Monitor: 21340

Screen: 10.1-inch IPS screen

Wireless Receiving: Built-in 2.4G wireless receiver

Picture Mode: 1/2/3/4 screen mode Operating Frequency: 2400-2483.5 MHz

Receiving Sensitivity: ? ?86 dB

Receiving Distance: Up to 200 m clear line of sight

Resolution: 1024×600

Color System: PAL / NTSC (Auto)

Brightness: 600 cd/m²

Load Dump Protection: ISO16750-2 Standard (Us=174V,

Ri=4?, Td=350ms)

Anti-Vibration Rate: GB/T 2423.56-2023 Standard (Random

5G vibration)

Operating Temperature: ?20 °C to +70 °C Storage Temperature: ?30 °C to +80 °C Operating Voltage: DC 11–32 V

Dimensions (L×W×T): $265 \times 168 \times 37 \text{ mm}$

Weight: 1840 g

Camera: 23311-C

Image Sensor: 1/3.7" color CMOS

Wireless Transmission: Built-in 2.4G digital wireless

transmitter with integrated antenna

Transmit Power: 18 dBm

Transmit Distance: Up to 200 m clear line of sight

Resolution: 1080P

Effective Pixels: 1920(H) x 1080(V)

Viewing Angle: 130° Infrared Distance: 10 m Shell Material: Aluminum alloy Waterproof Rating: IP69K Operating Voltage: DC 11–32 V

Operating Temperature: -20 °C to +60 °C Storage Temperature: -30 °C to +70 °C

Anti-Vibration Rate: GB/T 2423.56-2023 Standard (Random

5G vibration)

Outer Dimension (W×H×D): $106 \times 75 \times 70.4$ mm