

## Kamerasystem 9" 1080P Wireless inkl. kamera 23311-C QUAD 4CH

## SKU

28340-C

This is a complete wireless HD rear-view camera system with a 9-inch IPS monitor and a 1080P camera with a built-in antenna. It has up to 200 m transmission range in clear line of sight and uses automatic frequency hopping for a stable, interference-free signal. The monitor supports 1/2/3/4 split-screen display and features an intuitive OSD menu for mirror/normal image, scaling, and reverse delay. The camera has a 130° field of view, 10 m IR night vision, and IP69K waterproof rating for all-weather reliability.



## **Teknisk information**

Monitor: 21330

Screen: 9-inch IPS screen

Wireless Receiving: Built-in 2.4G wireless receiver

**Picture Mode:** 1 / 2 / 3 / 4 screen mode **Operating Frequency:** 2400–2483.5 MHz

Receiving Sensitivity: ? -86 dB

Receiving Distance: Up to 200 m clear line of sight

**Resolution:**  $1024 \times 600$ 

Color System: PAL / NTSC (Auto)

Brightness: 600 cd/m<sup>2</sup>

Load Dump Protection: ISO16750-2 Standard (Us=174V,

Ri=4?, Td=350ms)

Anti-Vibration Rate: GB/T 2423.56-2023 Standard (Random

5G vibration)

Operating Temperature: -20 °C to +70 °C Storage Temperature: -30 °C to +80 °C Operating Voltage: DC 11–32 V

Dimensions (LxWxT): 244 x 179 x 81 mm

Weight: 1140 g

Kamera: 23311-C

Image Sensor: 1/3.7" color CMOS

Wireless Transmission: Built-in 2.4G digital wireless

transmitter with integrated antenna

Transmit Power: 18 dBm

Transmit Distance: Up to 200 m clear line of sight

Resolution: 1080P

Effective Pixels: 1920(H) x 1080(V)

Viewing Angle: 130° Infrared Distance: 10 m Shell Material: Aluminum alloy Waterproof Rating: IP69K Operating Voltage: DC 11–32 V

Operating Temperature: -20 °C to +60 °C Storage Temperature: -30 °C to +70 °C

Anti-Vibration Rate: GB/T 2423.56-2023 Standard (Random

5G vibration)

Outer Dimension (W×H×D):  $106 \times 75 \times 70.4$  mm